

# F25

## INDUSTRIAL Radio Remote Controller

All New Series

### Safe-Reliable-Easy to use

- ▶ RF unit : Microprocessor controlled PLL synthesizer. Handheld type(160 channels), Joystick type(256 channels).
- ▶ RF Power : FCC part 15 ( 50mV/meter field strength. )
- ▶ FCC & Industry Canada certified.
- ▶ RF Approval : License-free in North America.
- ▶ Programmable function setting, suitable for diversified application.
- ▶ Pre-wiring standard cable for quick and easy installation.
- ▶ Durable casing with extra shock resistance.
- ▶ Temperature range : -40°C ~ +85°C.
- ▶ Operation range : Up to 100 meters.



 **TELECRANE**®

[www.telecrane.ca](http://www.telecrane.ca)

**KL.CRANES.INC**







# F25 All New Series

**TELECRANE**  
 Industrial Radio Remote Controller

Spec. Model	Function	Transmitter	Receiver
<b>F25</b> 2S/2D	2 Single / 2 Double Steps Buttons		
<b>F25</b> 4S/4D	EMS Button x 1	Power Supply : Four 1.5 Volts Batteries (AA size)	Power Supply : 24 / 48 / 110 / 220 / 380 VAC ( 50 / 60 Hz ) ( ± 20% ) or 12-24 VDC
<b>F25</b> 6S/6D	6 Single / 6 Double Steps Buttons		Dimension : 185 x 85 x 85 mm
<b>F25</b> 8S/8D	Start Button x 1		Weight : About 215 g w/o Batteries
<b>F25</b> 10S/10D	8 Single / 8 Double Steps Buttons w/1 Alarm Button	Power Indication : 3-Stage with LED Indicator	Dimension : 200 x 162 x 107 mm
	10 Single / 10 Double Steps Buttons w/1 Alarm Button		Weight : About 250 g w/o Batteries
<b>F25-60</b>	EMS Button x 1 Rotary Key x 1 5-Steps Joystick x 2 Single Step Buttons x 6 Select Switch x 4 ( 2 Steps x 2 / 3 Steps x 2 )		Dimension : 290 x 230 x 70 mm
		Dimension : 220 x 110 x 90 mm	Weight : About 1550 g w/o Cable
		Weight : About 995 g w/o Batteries	Weight : About 2200 g w/o Cable



## Optional Accessories



- Software CD
- USB Interface Cable



- Passive Antenna



- Copier



- Transmitter Protective Cover

